

Subsystem Description

1. Functional Architecture

Conceptually, the **On-board Computer** (OBC) acts as the brain governing the spacecraft, serving as the central component within the overall architecture of this system. It plays a pivotal role in a complex system that accommodates the following five distinct sub-modules: Electrical Power Supply (EPS), Communication System (COMMS), Attitude Determination and Control System (ADCS), and the payload (P/L).

In other words, the main purpose of the subsystem is to perform the housekeeping of the overall satellite. In this regard, performing both data processing and storage in a timely manner while maintaining a low power consumption is crucial so as to guarantee an efficient and robust performance of the PocketQube. In light of this, the **Flight Software** (FSW) running on the OBC needs then to be carefully designed by the application writer in order to meet the time requirements linked to the varied tasks that the satellite is expected to perform. A common technique used in embedded systems in order to fix this time constraint is implementing **Real-Time Operating Systems** (RTOS). In the PoCat project, **FreeRTOS** has been the open-source RTOS selected to manage the on-board FSW.

On the other hand, the OBC hardware needs to accommodate the FSW by providing enough resources for a correct execution. In summary, the breakdown of the OBC from the hardware perspective consists of a low-power but high-performance ARM Cortex M4 microprocessor, volatile and non-volatile memory banks for data storage, interfaces that reach out to peripherals and data buses interconnecting the whole system architecture.

To ensure the desired behaviour of the PocketQube, it is necessary for both software and hardware to converge seamlessly. This will enable the OBC to efficiently manage various tasks that play a critical role in determining the behavior of the picosatellite. In summary, the tasks that are performed by the On-Board Computer for the PoCat space mission are listed below:

- Task scheduling.
- Inter-task communication.
- Power management.
- Telecommand processing.
- Telemetry data handling.
- Payload data acquisition.
- Attitude determination and control.
- Error handling.

2. Requirements

Subsystem	ID	Requirement
OBC	OBC-0010	The OBC shall monitor all spacecraft subsystems.
OBC	OBC-0020	The OBC shall have a Scheduler which determines the execution of different tasks through time.
OBC	OBC-0030	The OBC shall provide and store the following housekeeping data: Satellite mode, Boot count, OBC error events, Internal satellite communication error events, RAM memory usage.
OBC	OBC-0040	The OBC shall retrieve and store housekeeping data for all spacecraft subsystems.
OBC	OBC-0050	The OBC shall monitor all satellite subsystems in order to verify their nominal behavior.
OBC	OBC-0060	The OBC shall execute TC received from the GSeg.
OBC	OBC-0070	The OBC shall be able to control and command all subsystems via its interfaces.
OBC	OBC-0080	The OBC shall retrieve and store scientific data from the Payload.
OBC	OBC-0090	The OBC shall have data interfaces with all subsystems.
OBC	OBC-0100	The OBC power supply voltage shall be 3.3 V.
OBC	OBC-0110	The OBC shall enable the manual transition between satellite modes if a TC from the ground is received.
OBC	OBC-0120	The OBC shall automatically transition between satellite modes based on battery levels.
OBC	OBC-0130	The OBC should allow in-orbit changes of its configuration.
OBC	OBC-0140	The OBC shall implement a command-less timer that triggers a recovery routine if a telecommand from the GS is not received after a certain period.

Subsystem	ID	Requirement
OBC	OBC-0150	The spacecraft shall allow modifications to the OBC Software after the satellite assembly is complete and while on ground.
OBC	OBC-0160	The spacecraft shall have a timer, set to a minimum of 30 minutes, before operations or deployment of the antennas.
OBC	OBC-0170	No radio emission shall be allowed after the spacecraft has been integrated within the PocketQube deployer until 45 minutes after deployment.

Revision #1
Created 15 November 2024 18:08:00 by artur.cot
Updated 15 November 2024 18:08:22 by artur.cot